



# SERIES A

A60

A80

A100

MODEL	A60	A80	A100
CUTTING WIDTH (mm)	600	800	1000
WEIGHT (Kg)	125	135	192
OIL PRESSURE (bar)	200	200	200
OIL FLOW (l/min)	20-50	20-50	30-80
NUMBER OF KNIVES	24	32	48
NUMBER OF HAMMERS	12	16	16
MAX CUTTING DIAMETER (mm)	20	20	35
DIMENSION A (mm)	680	680	680
DIMENSION B (mm)	60	800	1000
DIMENSION C (mm)	605	605	605



Direct transmission with motor inside the machine protected from impacts and collisions. Standard with high pressure oil seal.



Fluidbox for complete and safe engine management, with maximum shockproof valve, anti-cavitation system and flow regulation to set the rotor speed correctly.



Self-leveling support as standard that allows an oscillation of the equipment to accommodate the unevenness of the ground protecting it from bumps.



The machine comes standard in a two-pipe configuration, the fluidbox will manage the flow of oil coming from engine drainage. In the event that the back pressure at the discharge is greater than 8 bar, it's possible to provide for the third drainage tube for direct tank discharge.



Rotor can be equipped with knives for more shredding capacity and lower power requirement. Two-blade knife set for A60-A80. Knife set a three blades for A100. Rotor can be equipped with hammers for safely tackle shrubs up to 35mm in diameter.



Rear support roller adjustable in three positions for cutting height adjustment.



Rear roller and wear strip replaceable with rear protection with chains (**optional**).  
Useful in the case of cutting in both directions of travel, prepared to be installed as standard without modifications to the equipment.



Front protection with chains.  
Rear protection with wear-resistant rubber strip.



Available as an **option**: standard attachment and pins with measurements customized.



Standard with 1.6 m hydraulic hoses.  
Available as an **option**: set of hoses with customized lengths.



A60 - A80  
• Double knives  
• Light hammer



A100  
• Triple knives  
• Hammer