


SERIES BS

BS150
BS165
BS180
BS210

MODEL	BS150	BS165	BS180	BS210
BRUSH DIAMETER (mm)	560	560	560	560
WORKING WIDTH (mm)	1500	1650	1800	2100
WORKING WIDTH WITH BRUSH (mm)	1950	2100	2250	2550
WEIGHT (Kg)	400	425	450	500
PRESSURE (bar)	180	180	180	180
CAPACITY (lt)	450	480	510	560
SECTIONS	35	38	41	47
DIMENSION A (mm)	1425	1425	1425	1425
DIMENSION B (mm)	1688	1838	1988	2288
DIMENSION C (mm)	615	615	615	615



Engine supported by extension with bearings inside the machine.




Chain transmission.



Front protection e rubber side.



Standard with coupling for skid-steer, **optional**: custom coupling.




Available as **optional**: system of spraying water with electric pump e 100 liter tank for dust suppression.



Available as **optional**: wire side brush for cleaning road curbs, complete with pipes and engine.





Slotted brush support arm, to ensure constant resting on the ground and avoid damaging the brush unit.



Front roller connected to the collection bucket by hinges to facilitate cleaning of the machine. With rotor height adjustment to ensure a optimal functioning and compensate for progressive wear brushes. Replaceable Hardox lower blade e reversible.



Side brush, adjustable in 4 positions. High rest location and close to the machine for not occupy the roadway.



Polypropylene brush set or steel brushes for heavier jobs.