

FFL SERIES

FFL55

FFL75

MODEL (fixed teeth rotor)	FFL55	FFL75
CUTTING WIDTH (mm)	560	760
RECOMMENDED EXCAVATOR (ton)	2,5-4	3-5
WEIGHT	170	200
OIL PRESSURE (bar)	250	250
OIL FLOW (lt/min)	30-90	40-90
NUMBER OF TOOLS	12	16
MAX CUTTING DIAMETER (mm)	100	100
A DIMENSION (mm)	500	500
B DIMENSION (mm)	540	540
C DIMENSION (mm)	930	1130
EXCAVATOR ATTACHMENT WEIGHT (min-max Kg)	12-30	12-30



Fluidbox for complete and safe engine management, with maximum shockproof valve, anti-cavitation system and flow regulation to set the rotor speed correctly.



Double-bottomed case to increase robustness and optimize the cutting volume. Internal wearresistant lining in Hardox.



Replaceable wear-resistant skid with a large surface of support.



Predisposition of holes for a customized positioning of the attachment.



Standard with 3mt hydraulic hoses. Available as **optional**: set of hoses with customized lengths.



Standard replaceable tool with cutting edge in widia.




Plus replaceable tool with cutting edge in widia.



Available as **optional**: standard attachment and pins with customized measurements, flat plate for attachment as standard.



Replaceable tool with double point and cutting edge in widia.



Steel alloy tool for cutting depth reducer rotor.



As standard on FFL series: cutting depth reducer that allows the rotor to keep a constant number revolutions and to preserve tool life.



Gr2 gear motor with direct transmission to maximize the transmitted power.
Available as **Optional**: Gr3 gear motor
Available as **Optional**: piston motor



Fixed teeth rotor with interchangeable tools designed for heavy jobs.



Thumb to move shrubs and branches.